Low Profile (LP) Tank



The Fireflex Low Profile (LP) Tank is a perfect water relay tank in rural areas or in any situation where water access is an issue. It is fully self-supporting, has an open-top design and has a wide collar for easy filling. Fireflex LP Tanks enable fire departments still obtain enough water for effective firefighting to use in isolated areas.

It is lighter and safer than traditional framed tanks and is easy to deploy by only one person. It is quickly filled from a water tender in mere minutes. With its versatility, the LP Tank can be used in remote site locations or can act as a water reservoir placed close to the fireline.

Design Features

- No parts to assemble;
- Easily and quickly deployed by just one person;
- Frameless tank constructed of durable, lightweight yet high-strength fabric, which is mold- and mildewresistant;
- The foam-filled collar eliminates the need for inflation and will rise automatically when filling;
- Multi-point tie down system for secure grounding;
- Fast, easy filling from water tenders;
- Lifting strap inside the center of the tank allows for easy cleaning and drying;
- Fast discharge through a standard 3" NPT outlet;
- Low maintenance, easy to clean and repair; and
- Compact for easy storage, fits inside a standard vehicle for transport, provides long-term water storage.







Add-Ons and Accessories

- Ball valves / fittings;
- Ground pads;
- Transport bags;
- Repair kits;
- Drainage outlets: 1" to 6" NPT; and
- Secondary internal impact pads available for large size tanks.

Applications

- Water relay tank;
- Long- or short-term water storage; or
- Protection of urban interface exposures.

Please note: If using your tank exclusively for mixing foam and/or retardants, please use the Fireflex Hazmat tank.

Low Profile (LP) Tank



LP Tank



Multi-point tie down system for secure grounding during operations.



The tank can be easily folded by just one person.



The LP Tank is perfect for structural firefighting.

Specifications

Model	Capacity		Collapsible Dimension (L x W x H)		Weight		Outer Filled Diameter		Inner Collar Diameter		Filled Height		3" NPT Outlet
	USG	L	IN	CM	LB	KG	IN	CM	IN	СМ	IN	СМ	#
FFTF1012LP	1,200	4,546	15 x 24 x 38	38 x 61x 100	68	31	128	325	82	210	34	86	1
FFTF1518LP	1,800	6,800	15 x 24 x 44	38 x 61 x 112	75	34	154	390	102	260	36	91	1
FFTF2024LP	2,400	9,100	16 x 30 x 50	41 x 76 x 127	85	38	180	460	128	325	34	86	1
FFTF2530LP	3,000	11,340	18 x 29 x 48	46 x 74 x 122	100	45	188	480	132	335	38	96	1
FFTF3036LP	3,600	13,600	20 x 29 x 48	51 x 74 x 122	115	52	189	480	144	366	38	96	1
FFTF4048LP	4,800	18,200	26 x 32 x 48	66 x 81 x 122	150	68	224	569	164	416	42	107	1

Specifications are approximate and subject to change.