

# Insta-Berm® (Swift Slide)



The Insta-Berm (Swift Slide) is the newest addition to SEI's lineup of spill containment berms. With aluminum wall supports built into the berm liner, the berm walls can be raised in seconds by sliding the supports into place. Not only does the Swift Slide reduce assembly and disassembly time, operators no longer need to worry about loose parts being damaged or lost. The Insta-Berm (Swift Slide) is a one piece system that provides secondary containment in any environment.

## **Design Features**

- One piece system, wall supports are built into the berm;
- Rapid assembly time without the use of any tools;
- Provides high volume secondary containment for fuel tanks, drums, generators, pumps, vehicles and more;
- Vehicles can easily be driven in and out by quickly assembling/disassembling the wall(s);
- Fully collapsible, easily transportable;
- No loose pieces for operators to lose;
- Available in a variety of sizes with a 12" wall.



## **Berm Options**

- Groundsheets are recommended to lay between the berm and the ground to protect the berm liner;
- Track belting is available to protect the berm from heavy wheel damage;
- High-wind stakes can anchor the berm to the ground through optional eyelet patches;
- Compatible with an optional RainDrain™ or Spill Monkey filtration system, that allows rainwater to drain out of the berm while capturing hydrocarbons and additives;

## **Fabric Options**

**Chem-Shield** – Sturdy and abrasion resistant, the Chem-Shield™ fabric is suitable for a variety of chemicals and is cold crack resistant to -34°C.

**Arctic-Shield** – Certified to CAN/ULC-S668, Arctic-Shield™ Lightweight and Heavyweight fabric features chemical and fire resistant properties and is cold crack resistant to -50°C (not suitable for acids). In addition to superior abrasion resistance, Arctic-Shield Heavyweight remains flexible in freezing temperatures making it ideal for set up in the winter.

# Insta-Berm® (Swift Slide)



Model	Capacity		Deployed Dimensions (L x W x H)		Shipping Weight	
	USG	L	IN	CM	LB	KG
IBSS101012	748	2831	10' x 10' x 12"	304 x 304 x 30	40.0	18.1
IBSS101512	1122	4247	10' x 15' x 12"	304 x 457 x 30	56.0	25.4
IBSS102012	1496	5662	10' x 20' x 12"	304 x 609 x 30	71.0	32.2
IBSS152012	2244	8494	15' x 20' x 12"	457 x 609 x 30	96.0	43.5
IBSS153012	3366	12741	15' x 30' x 12"	457 x 914 x 30	138.0	62.6
IBSS154012	4488	16988	15' x 40' x 12"	457 x 1219 x 30	179.0	81.2
IBSS202012	2992	11325	20' x 20' x 12"	609 x 609 x 30	124.0	56.2
IBSS203012	4488	16988	20' x 30' x 12"	609 x 914 x 30	176.0	79.8
IBSS204012	5984	22651	20' x 40' x 12"	609 x 1219 x 30	228.0	103.4
IBSS205012	7480	28314	20' x 50' x 12"	609 x 1524 x 30	276.0	125.2